

CSB 1100CL

1.3 Mega Pixel CMOS B/W Video Camera with CameraLink Interface



- **CameraLink output**
- **High resolution 1240 (H) x 1023 (V)**
- **Various shutter modes including**
 - Global shutter - all pixels simultaneously exposed
 - Random Trigger Shutter (RTS)
- **WOI-function**
Up to 16 arbitrary rectangular areas (region of interest) can be read out with increase frame rate
- **Sub-sampling**
Allows the output of an image with an increase frame rate at a lower resolution
- **High dynamic range**
By adjustable sensitivity characteristic
- **Application**
 - High end machine vision
 - Factory automation
 - Microscopy
 - Quality control


Technical Data

Type

CSB 1100CL

Image sensor	CMOS Image sensor, monochrome
Total pixel	1280 (H) x 1024 (V)
Active pixel	1240 (H) x 1023 (V)
Pixel size	6.7 µm(H) x 6.7 µm(V)
Image Area	8.31 x 6.85 mm
Driving frequency	33MHz
Scanning line	1023 lines Progressive Scan
Frame rate	22.9fps (full resolution) 83 fps (640x480)
Sync system	Internal
Digital output	CameraLink (10bit 33.0MHz)
WOI-function	Output of up to 16 WOI with increased frame rate
Signal / Noise ratio	>50dB
Input signal	Trigger, CLOCK, COMMAND, Exposure control
Output signal	CLOCK 33.00000MHz +/-100ppm (Internal-sync)
Sensitivity setting	FIX (FIX GAIN)
by external signal	PGC (PROGRAMABLE GAIN CONTROL)
Gamma	1.0 Fix
Shutter modes	Random trigger shutter, Synchronized global shutter, Rolling shutter
Power source	DC12V plus/minus 10% (ripple <100mV(p-p))
Power consumption	Approx. 1.3 W
Ambient condition	Temperature: -10°C~50°C Humidity: 20%~80%
Lens mount	C-mount (optional TFL-mount)
External dimension	44 (W) x 29 (H) x 52 (D)mm
Weight	Approx. 200 g
Accessories	<ul style="list-style-type: none"> • Data Cable with double-terminated connector (3m) • Tripod mounting kit • IR cut filter

Dimension



NEW ELECTRONIC TECHNOLOGY Vertriebs-GmbH

Lerchenberg 7 • D 86923 Finning, Germany • Phone: +49(0)88 06 - 92 34-0 • Fax: +49(0)88 06 - 92 34-77

E-mail: info@net-gmbh.com

NET USA, Inc.

3037-45th Street #8 • Highland, IN 46322 • Phone: (219) 934-9042 • Fax: (219) 934-9047

E-mail: netusa@bellsouth.net

www.net-gmbh.com